



**But à souder**  
*Welding tips*

DN		Dimensions (mm)		
		D	d	L
3/8"	10	12,0	9,0	33,0
1/2"	13	12,0	9,0	36,0
3/4"	20	18,0	15,0	45,0
1"	25	25,0	22,5	49,5
1"1/4	32	32,0	30,0	49,5
1"1/2	38	38,0	35,5	51,0
2"	50	51,0	48,5	58,0
2"1/2	63	63,5	60,5	69,0
3"	76	76,0	72,8	69,0
4"	100	104,0	100,0	76,0

Embout ASME BPE-2012 / ASME BPE-2012 nozzles

DN		Dimensions (mm)		
		D	d	L
1/2"	13	12,70	9,40	46,00
3/4"	20	19,05	15,75	55,00
1"	25	25,40	22,10	49,00
1"1/2	38	38,10	34,80	58,00
2"	50	50,80	47,50	58,00
2"1/2	63	63,50	60,20	69,00
3"	76	76,20	72,90	69,00
4"	100	101,60	97,38	76,00

(C) : Références avec embout rallongé pour montage coquille, dimension L différente  
Reference with longer nipples for reusable ferrules assembly, L dimension differs

La forme et la dimension des pièces sont données à titre indicatif, elles peuvent être modifiées sans préavis.  
The shape and the dimensions of the items are purely indicative, they can change without notice.